



D E L E T E X

Leather & Textiles

DYNACTIV 675

Composition:	Topcoat:	100 % PVC
	Backing:	67 % PES 33 % CO
Colour range:	32	
Weight:	710 gr/m ² +/- 70	
Thickness:	1.10 mm +/- 0.10	
Roll width:	140 cm	
Roll length:	+/- 30 lm	

Description:


Dynactiv 675 is an artificial leather especially designed for outdoor usage and applications for healthcare. The material has the look of textile, with the advantages of artificial leather.

Technical aspects:

Lightfastness:	DIN 54004	Min 6 blue scale
Abrasion resistance:	EN ISO 5470-2	125 000 cycles (Martindale)
Adhesion of the finish:	EN ISO 2411	Warp: Min 30 N Weft: Min 20 N
Tear strength:	EN ISO 4674-1	Warp: Min 20 N Weft: Min 18 N
Elongation:	EN ISO 1421	Warp: +/- 62 % Weft: +/- 190 %
Tensile strength:	EN ISO 1421	Warp: Min 300 N Weft: Min 240 N


Deletex nv – Brabantstraat 91 – B-8790 Waregem

T. +32 (0) 56 42 23 03 – F. +32 (0) 56 42 44 32 – commercial@deletex.com



D E L E T E X

Leather & Textiles

Fire retardancy: EN1021 1 – 2
NF-P 92-503 M2
BS5852 crib 5
IMO  Res. MSC.307 (88)

Extra: Effective against fungus and bacteria
Resistant to blood and urine
Phthalate-free

Cleaning instructions: Clean with a lye of warm water and mild natural soap, using a micro-fiber cloth. Please do not use products containing alcohol, solvents, chloride, chemical cleaning agents or detergents.

Deletex nv – Brabantstraat 91 – B-8790 Waregem

T. +32 (0) 56 42 23 03 – F. +32 (0) 56 42 44 32 – commercial@deletex.com