

**D E L E T E X**

Leather & Textiles

## **VALENCIA**

Composition:	Topcoat:	100 % PVC
	Backing:	100 % PES
Colour range:		60
Weight:		650 gr/m <sup>2</sup> +/- 65
Thickness:		1.10 mm +/- 0.16
Roll width:		137 cm
Roll length:		+/- 30 lm

### **Description:**


Valencia is most surprising with its high Martindale: 300.000 cycles. The extreme large pallet in colours inspires every designer to find the correct combination.

### **Technical aspects:**

Lightfastness:	DIN 54004	Min 7 blue scale
Abrasion:	EN ISO 12947	300 000 cycles (Martindale)
Adhesion of the finish:	EN ISO 2411	Ketting: Min 26 N
		Inslag: Min 26 N
Tear strength:	EN ISO 4674-1	Ketting: Min 32 N
		Inslag: Min 31 N
Stitching strength:	DIN 54301	Ketting: Min 58 N
		Inslag: Min 39 N
Elongation:	EN ISO 1421	Ketting: +/- 51 %
		Inslag: +/- 149 %
Tensile strength:	EN ISO 1421	Ketting: Min 389 N
		Inslag: Min 238 N


Deletex nv – Brabantstraat 91 – B-8790 Waregem

T. +32 (0) 56 42 23 03 – F. +32 (0) 56 42 44 32 – commercial@deletex.com



**D E L E T E X**

Leather & Textiles

Fire retardancy: EN1021 1 – 2  
NF-P 92-503 M2  
FMVSS 302  
ECE R 118  
IMO  Res. MSC.307 (88)

Extra: Antimicrobial Antifungal protection  
Antibacterial protection  
Antimycotic protection.

Mildew resistant

Antistatic

Resistant to blood

Resistant to urine

PERMABLOK® protective finish 

Cleaning instructions: Clean with a lye of warm water and mild natural soap, using a micro-fiber cloth. Please do not use products containing alcohol, solvents, chloride, chemical cleaning agents or detergents.

Deletex nv – Brabantstraat 91 – B-8790 Waregem

T. +32 (0) 56 42 23 03 – F. +32 (0) 56 42 44 32 – commercial@deletex.com