

Automotion



Sistema Qualità certificato
ISO 9001:2008 rev. n° 182/04
ISO 9001:2008 rev. n° 182/07

mod.4.10.1.11

DELETEX



LAB REPORT

TEST	METHOD	REQUIREMENTS	RESULTS
THICKNESS	IUP 4	1,0 - 1,4 mm	1,12
RUBBING TEST			
DRY 2000 CYCLES	IUF 450	≥ 4-5 GREY SCALE	5
WET 500 CYCLES	IUF 450	≥ 4-5 GREY SCALE	5
FLEX RESISTANCE	DIN 53351	25000 CYCLES	pass
DRY ADHESION	IUF 470	> 3 N	5,6
TABER CS 10 1 KG	ASTM D-1175	500 CYCLES	pass
FOGGING	DIN 75201	< 7 mg	4,5
TEAR STRENGTH	IUP 8	≥ 15 N/mm	29,5
LIGHT FASTNESS	DIN 75202	≥ 3 GREY SCALE	4-5
FLAMMABILITY	FMVSS 302	<100 MM/MIN	0

QUALITY MANAGER
PASUBIO SPA
PAOLO ZEGGIO

Deletex nv
Rekkemstraat 64/0001
8930 Lauwe
België
T. +32/(0)56.42.23.03
F. +32/(0)56.42.44.32
info@deletex.com
www.deletex.com

Deletex
LEATHER & TEXTILES